

Keymix Keylectrolytes Key 56 Electrolyte Replacers International Animal Health Products Pty Ltd

Chemwatch: **36-7563** Version No: **8.1**

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 23/12/2022 Print Date: 09/10/2023 S.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	eymix Keylectrolytes Key 56 Electrolyte Replacers	
Chemical Name	Applicable	
Synonyms	Keylectrolytes	
Chemical formula	Not Applicable	
Other means of identification	Care Products Group Standard 2006, HSR002521; Animal Nutritional and Animal, New Zealand HSNO Approval	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses An electrolyte replacer for broiler chickens, starter pullets and layer hens.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	International Animal Health Products Pty Ltd	
Address	18 Healey Circuit Huntingwood NSW 2148 Australia	
Telephone	+61 2 9672 7944	
Fax	+61 2 9672 7988	
Website	www.iahp.com.au	
Email	info@iahp.com.au	

Emergency telephone number

Association / Organisation	ustralian Poison Information Centre	
Emergency telephone numbers	13 11 26 (24 Hours)	
Other emergency telephone numbers	New Zealand: National Poisons Centre 0800 764 766 (24 hours)	

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable	
Classification ^[1]	erious Eye Damage/Eye Irritation Category 2B	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Issue Date: 23/12/2022 Print Date: 09/10/2023

Keymix Keylectrolytes Key 56 Electrolyte Replacers

Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Warning

Hazard statement(s)

AUH066	Repeated exposure may cause skin dryness and cracking.	
H320 Causes eye irritation.		

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

P264	Wash all exposed external body areas thoroughly after handling.
Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing	
P337+P313	If eye irritation persists: Get medical advice/attention.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7447-40-7	30-60	potassium chloride
Not Available	balance	Ingredients determined not to be hazardous
Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. 			
Skin Contact	ontact occurs: iediately remove all contaminated clothing, including footwear. h skin and hair with running water (and soap if available). k medical attention in event of irritation.			
Inhalation	f fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.			
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. 			

• Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	-------------------------------------------------------------------------------------------------------------------------------------------

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 	
Fire/Explosion Hazard	 Equipment should be thoroughly decontaminated after use. Non combustible. Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of: carbon monoxide (CO) carbon dioxide (CO2) hydrogen chloride phosgene other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes. 	
HAZCHEM	Not Applicable	

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Use dry clean up procedures and avoid generating dust. Place in a suitable, labelled container for waste disposal.
Major Spills	 Moderate hazard. CAUTION: Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing. Prevent, by any means available, spillage from entering drains or water courses. Recover product wherever possible. IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal. ALWAYS: Wash area down with large amounts of water and prevent runoff into drains. If contamination of drains or waterways occurs, advise Emergency Services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

	Avoid all personal contact, including inhalation.
	 Wear protective clothing when risk of exposure occurs.
	▶ Use in a well-ventilated area.
	Prevent concentration in hollows and sumps.
	 DO NOT enter confined spaces until atmosphere has been checked.
	DO NOT allow material to contact humans, exposed food or food utensils.
	Avoid contact with incompatible materials.
	When handling, DO NOT eat, drink or smoke.
	Keep containers securely sealed when not in use.
	Avoid physical damage to containers.
	Always wash hands with soap and water after handling.
	Work clothes should be laundered separately. Launder contaminated clothing before re-use.
	 Use good occupational work practice.
	 Observe manufacturer's storage and handling recommendations contained within this SDS.
	 Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
	 Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions)
Safe handling	 Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. Establish good housekeeping practices.
	Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.
	• Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention
	should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion. Accordin to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.
	Do not use air hoses for cleaning.
	Minimise dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Vacuums with explosion-proof motors should be used.
	 Control sources of static electricity. Dusts or their packages may accumulate static charges, and static discharge can be a source of ignition.
	 Solids handling systems must be designed in accordance with applicable standards (e.g. NFPA including 654 and 77) and other national guidance.
	Do not empty directly into flammable solvents or in the presence of flammable vapors.
	 The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static observes.
	charges. Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in
	the presence of an appropriate ignition source.
	Do NOT cut, drill, grind or weld such containers.
	In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.
	 Store in original containers. Keep containers securely sealed.
	 Store in a cool, dry area protected from environmental extremes.
	 Store away from incompatible materials and foodstuff containers.
	 Protect containers against physical damage and check regularly for leaks.
Other information	 Observe manufacturer's storage and handling recommendations contained within this SDS.
	For major quantities:
	 Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including
	stormwater, ground water, lakes and streams}.
	 Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require
	consultation with local authorities.

Conditions for safe storage, including any incompatibilities

Suitable container	 Cardboard carton with plastic liner; multiwalled paper bag with plastic liner. Check that containers are clearly labelled Packaging as recommended by manufacturer.
Storage incompatibility	 Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
Keymix Keylectrolytes Key 56 Electrolyte Replacers	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
potassium chloride	Not Available		Not Available	

Exposure controls

	None required when handling small quantities. OTHERWISE:				
	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.				
	The basic types of engineering controls are:				
	Process controls which involve changing the way a job activi	ty or process is done to reduce the risk.			
	Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation				
	that strategically "adds" and "removes" air in the work enviro				
	designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.				
	 Local exhaust ventilation is required where solids are has large, a certain proportion will be powdered by mutual fri 		articulates are relatively		
	 If in spite of local exhaust an adverse concentration of th considered. 	e substance in air could occur, respiratory p	protection should be		
	Such protection might consist of:				
	(a): particle dust respirators, if necessary, combined with an				
	(b): filter respirators with absorption cartridge or canister of the right type;				
	 (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess varyin 	a "escape" velocities which in turn determ	ine the "capture		
Appropriate engineering	velocities" of fresh circulating air required to effectively remo				
controls	Type of Contaminant:		Air Speed:		
	direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion)	conveyer loading, crusher dusts, gas	1-2.5 m/s (200- 500 f/min.)		
	grinding, abrasive blasting, tumbling, high speed wheel get velocity into zone of very high rapid air motion).	nerated dusts (released at high initial	2.5-10 m/s (500- 2000 f/min.)		
	Within each range the appropriate value depends on:				
	Lower end of the range	Upper end of the range			
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents			
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity			
	3: Intermittent, low production.	3: High production, heavy use			
	4: Large hood or large air mass in motion	4: Small hood-local control only			
	Simple theory shows that air velocity falls rapidly with distant	ce away from the opening of a simple extra	ction pipe. Velocity		
	generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the				
	extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the				
	extraction fan, for example, should be a minimum of 4-10 m/ metres distant from the extraction point. Other mechanical co	. ,	•		
		onsiderations, producing periornalice delic	ווס איונוווו נווכ כגנומטנוטוו		

metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment

Eye and face protection



No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE:

Safety glasses with side shields.

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] Skin protection See Hand protection below No special equipment needed when handling small quantities. Hands/feet protection OTHERWISE: Wear chemical protective gloves, e.g. PVC. **Body protection** See Other protection below No special equipment needed when handling small quantities. OTHERWISE: Other protection Overalls. Barrier cream. Eyewash unit.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

• The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

• Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

• Use approved positive flow mask if significant quantities of dust becomes airborne.

· Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	White to off-white free flowing powder; mixes wi	White to off-white free flowing powder; mixes with water. Bulk density: 1.00-1.2 g/mL			
Physical state	Divided Solid	Relative density (Water = 1)	Not Available		
Odour	Not Available	Partition coefficient n- octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable		
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available		
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable		
Initial boiling point and	Not Available	Molecular weight (g/mol)	Not Applicable		

boiling range (°C)			
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

	al ellects				
Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.				
Ingestion	Acute potassium poisoning after swallowing is rare, because von	Accidental ingestion of the material may be damaging to the health of the individual. Acute potassium poisoning after swallowing is rare, because vomiting usually occurs and renal excretion is fast. Potassium causes a slow, weak pulse, irregularities in heart rhythm, heart block and an eventual fall in blood pressure.			
Skin Contact	Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. Irritation and skin reactions are possible with sensitive skin Open cuts, abraded or irritated skin should not be exposed to this material				
Eye	Limited evidence or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals. Prolonged eye contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).				
Chronic	Prolonged or repeated skin contact may cause drying with cracki Substance accumulation, in the human body, may occur and may occupational exposure. Long term exposure to high dust concentrations may cause chan less than 0.5 micron penetrating and remaining in the lung.	y cause some concern following repeated or long-term			
Keymix Keylectrolytes Key	ΤΟΧΙΟΙΤΥ	IRRITATION			
56 Electrolyte Replacers	Not Available	Not Available			
notooline obtende	ΤΟΧΙΟΙΤΥ	IRRITATION			
potassium chloride	Oral (Rat) LD50: 2600 mg/kg ^[2]	Eye (rabbit): 500 mg/24h - mild			

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.

Issue Date: 23/12/2022 Print Date: 09/10/2023

Keymix Keylectrolytes Key 56 Electrolyte Replacers

Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

POTASSIUM CHLORIDE	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.			
Acute Toxicity	×	Carcinogenicity	×	
Skin Irritation/Corrosion	×	Reproductivity	×	
Serious Eye Damage/Irritation	*	STOT - Single Exposure	×	
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×	
Mutagenicity	×	Aspiration Hazard	×	

Data available to make classification

SECTION 12 Ecological information

Toxicity

Keymix Keylectrolytes Key 56 Electrolyte Replacers	Endpoint	Test Duration (hr)	Species	Value	Source	
	Not Available	Not Available	Not Available	Not Available	Not Available	
	Endpoint	Test Duration (hr)	Species	Value	Source	
	EC50	72h	Algae or other aquatic plants	>100mg/l	2	
	EC50	48h	Crustacea	93mg/l	4	
potassium chloride	EC50	96h	Algae or other aquatic plants	894.6mg/L	4	
	LC50	96h	Fish	390mg/l	4	
	NOEC(ECx)	25h	Fish	9.319mg/L	4	
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic To					
	4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
potassium chloride	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
potassium chloride	LOW (LogKOW = -0.4608)

Mobility in soil

Ingredient	Mobility
potassium chloride	LOW (KOC = 14.3)

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws
disposal	operating in their area. In some areas, certain wastes must be tracked.
	A Hierarchy of Controls seems to be common - the user should investigate:
	▶ Reduction
	▶ Reuse

▶ Recycling
Disposal (if all else fails)
This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf
life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use,
and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.
DO NOT allow wash water from cleaning or process equipment to enter drains.
It may be necessary to collect all wash water for treatment before disposal.
In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
Where in doubt contact the responsible authority.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
potassium chloride	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
potassium chloride	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

potassium chloride is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (potassium chloride)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes

Issue Date: 23/12/2022 Print Date: 09/10/2023

Keymix Keylectrolytes Key 56 Electrolyte Replacers

National Inventory	Status
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	23/12/2022
Initial Date	02/09/2013

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard **OSF: Odour Safety Factor** NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Notes

New Zealand HSNO approval number HSR002521. Animal Nutritional and Animal Care Products Group Standard 2017

New Zealand HSNO Approval: HSR002521; Animal Nutritional and Animal Care Products Group Standard 2017